

FCV100

FOOT CONTROLLER

Technical Specifications

Version 1.2 August 2003

ENGLISH



www.behringer.com



JUST LISTEN.

FOOT CONTROLLER FCV100

FOOT CONTROLLER

Ultra-Flexible Dual-Mode Foot Pedal for Volume and Modulation Control

- ▲ Volume control of one stereo or two individual musical instruments
- ▲ Dedicated modulation function for direct connection to keyboard's modulation control input
- ▲ VCA control for utmost reliability and smooth audio performance
- ▲ Adjustable minimal volume
- ▲ Standard 9 V battery or 12 V DC adapter operation (not included)
- ▲ Battery low indicator
- ▲ Ultra-compact, road-suitable housing
- ▲ High-quality components and exceptionally rugged construction ensure long life and durability
- ▲ Designed in Germany. Manufactured under ISO9000 certified management system

FOOT CONTROLLER FCV100

SPECIFICATIONS

Input/output	1/4" TS connectors, unbalanced <u>Tip</u> : Supply voltage from unit/instrument to be controlled (Impedance: 50 k Ω) <u>Ring</u> : Slider pick-up (control voltage dependend on pedal position (Impedance: 0...50 k Ω))
Maximum input level	2 V (RMS)
Input impedance	300 k Ω
Output impedance	560 Ω
Attenuation range	0 - 70 dB
Total harmonic distortion	0.04% (1 kHz @ 1 V (RMS) output)
Signal-to-noise ratio	94 dB
Power supply	12 V / >10 mA DC power adapter
Battery power	9 V battery type 6LR91
Power consumption	7 mA
Dimensions	6" (150 mm) x 5" (130 mm) x 2 3/8" (60 mm)
Weight	approx. 650 g (1.43 lbs)

The information contained in this publication is subject to change without notice. No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of BEHRINGER Spezielle Studiotechnik GmbH.

BEHRINGER is a registered trademark. ALL RIGHTS RESERVED.

© 2003 BEHRINGER Spezielle Studiotechnik GmbH.

BEHRINGER Spezielle Studiotechnik GmbH, Hanns-Martin-Schleyer-Str. 36-38,
47877 Willich-Münchheide II, Germany

Tel. +49 2154 9206 0, Fax +49 2154 9206 4903
