

GM108

V-TONE

Technical Specifications

Version 1.0 July 2003

ENGLISH



www.behringer.com



V-TONE

True Analog Modeling 15-Watt Guitar Amp with 8" Speaker

- ▲ Extremely versatile practice amplifier with authentic analog amp modeling
- ▲ Original 20-Watt vintage-design guitar speaker
- ▲ Authentic Analog Modeling for 3 classic guitar amps, 3 speaker simulation models plus 3 gain modes—providing you with 27 classic sound presets
- ▲ Wide-range drive control for super-fat sounds with any pickup types
- ▲ Dedicated 3-band EQ and master level control
- ▲ CD input allows you to play along with your favorite music
- ▲ Powerful headphone output with speaker simulation
- ▲ Rugged construction for years of trouble-free use
- ▲ Designed in Germany. Manufactured under ISO9000 certified management system

GM108

SPECIFICATIONS

AUDIO INPUTS

Guitar input	
Connector	1/4" TS mono connector
CD input	
Connector	1/4" TRS stereo connector

AUDIO OUTPUTS

Headphone output	
Connector	1/4" TRS stereo connector

SYSTEM SPECIFICATIONS

Power amp output	15 Watts RMS into 4 Ohms
------------------	--------------------------

LOUDSPEAKER

Type	8" vintage design guitar speaker
Impedance	4 Ohms
Power handling	20 Watts

POWER SUPPLY

Mains voltage	
USA/Canada	120 V~, 60 Hz
Europe/U.K./Australia	230 V~, 50 Hz
Japan	100 V~, 50 - 60 Hz

DIMENSIONS/WEIGHT

Dimensions (H x W x D)	approx. 322 mm (13 1/8") x 357 mm (14 1/16") x 162 mm (6 3/8")
Weight	approx. 5.15 kg (11 lbs. 3 oz.)

The information contained in this manual is subject to change without notice. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of BEHRINGER Spezielle Studiotechnik GmbH.

BEHRINGER is a registered trademark. ALL RIGHTS RESERVED.

© 2003 BEHRINGER Spezielle Studiotechnik GmbH.

BEHRINGER Spezielle Studiotechnik GmbH, Hanns-Martin-Schleyer-Str. 36-38, 47877 Willich-Münchheide II, Germany
Tel. +49 2154 9206 0, Fax +49 2154 9206 4903
