

K3000FX

ULTRATONE

Specifications

Version 1.1 April 2006



www.behringer.com



ULTRATONE

Ultra-Flexible 300-Watt 4-Channel PA System / Keyboard Amplifier with FX and FBQ Feedback Detection

- ▲ Ultra-flexible 300-Watt 4-channel PA System / Keyboard Amplifier
- ▲ Powerful 15" BUGERA™ woofer and custom-made 1" driver for ultimate sound reproduction
- ▲ Integrated 24-bit digital FX processor with 100 awesome presets including reverb, chorus, flanger, delay, pitch shifter and various multi-effects
- ▲ Revolutionary FBQ Feedback Detection System instantly reveals critical frequencies
- ▲ Full 4-channel stereo operation with separate Volume and FX Send per channel
- ▲ Additional XLR mic input on Channel 1 for direct connection of dynamic microphones
- ▲ Dedicated 7-band graphic EQ for awesome sound shaping
- ▲ Balanced stereo XLR DI with Ground Lift switch for direct connection to your mixing console
- ▲ Main section with FX Return level, Master Volume, Phones level and Shape switch
- ▲ Link output allows linking to a slave amplifier for true stereo operation
- ▲ Subwoofer output for ultimate low-end power
- ▲ CD input allows you to play along to your favorite music
- ▲ Separate headphone output—perfect for quiet practicing
- ▲ High-quality components and exceptionally rugged construction ensure long life
- ▲ Conceived and designed by BEHRINGER Germany

K3000FX

SPECIFICATIONS

AUDIO INPUTS	
Line In 1 - 4	1/4" TS connector
Input impedance	approx. 30 kΩ balanced
Stereo Link In	1/4" TS connector
Input impedance	approx. 20 kΩ unbalanced
CD In/Aux In	RCA connector
Input impedance	approx. 20 kΩ unbalanced
Mic In 1	XLR connector
Input impedance	approx. 2 kΩ balanced
AUDIO OUTPUTS	
Headphones connector	1/4" TRS connector
Line Out	1/4" TS and XLR connector
Output impedance	1/4" TS connector: approx. 150 Ω unbalanced XLR connector: approx. 300 Ω balanced
Stereo Link Out	1/4" TS connector
Output impedance	approx. 150 Ω unbalanced
Sub Out	1/4" TS connector
Output impedance	approx. 150 Ω unbalanced
EQUALIZER	
Type	Graphic EQ with FBQ Feedback Detection
Frequency range	63 Hz / 160 Hz / 400 Hz / 1 kHz / 2.5 kHz / 6.3 kHz / 12 kHz
Bandwidth	2/3-oct.
Control range	+12 to -12 dB
DIGITAL EFFECTS PROCESSOR	
Converters	24-bit sigma-delta, 64/128-times oversampling
Sampling rate	40 kHz
SYSTEM SPECIFICATIONS	
Power amp output	300 Watts
LOUDSPEAKER	
Type	15" BUGERA™ woofer and custom-made 1" driver
Input impedance	4 Ω
POWER SUPPLY	
Mains voltage	USA/Canada 120 V~, 60 Hz U.K./Australia 230 V~, 50 Hz Europe 230 V~, 50 Hz China/Korea 220 V~, 50 Hz Japan 100 V~, 50 - 60 Hz
General export model	120/230 V~, 50 - 60 Hz
Power consumption	approx. 350 Watts
Fuse	100 - 120 V~: 6.3 A H 250 V
	220 - 240 V~: 3.15 A H 250 V
Mains connection	Standard IEC receptacle
DIMENSIONS/WEIGHT	
Dimensions	approx. 530 mm (20 7/8") x 597 mm (23 1/2") x 406 mm (16")
Weight	approx. 29.5 kg (65.04 lbs.)

Technical specifications and appearance subject to change without notice. The information contained herein is correct at the time of printing. The names of companies, institutions or publications pictured or mentioned and their respective logos are registered trademarks of their respective owners. Their use neither constitutes a claim of the trademarks by BEHRINGER® nor affiliation of the trademark owners with BEHRINGER®. BEHRINGER® accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph or statement contained herein. Colours and specification may vary slightly from product. Products are sold through our authorised dealers only. Distributors and dealers are not agents of BEHRINGER® and have absolutely no authority to bind BEHRINGER® by any express or implied undertaking or representation. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of BEHRINGER Spezielle Studiotechnik GmbH. BEHRINGER® is a registered trademark.