

David Series

Model	Power	Peak Power	Power Mono Bridge	Power Handling	Speakers	Tweeters	Crossover	Frequency Response	Sensitivity	Impedance	Dimensions	Weight	Coverage	Distortion
CX110	N/A	N/A	N/A	200W RMS	CX1060C8	COAX	4KHz @18dB	36Hz-20KHz	98dB SPL@1W1M	8Ω	15.25"W X 16"H X 14.5"D	26 LBS	100°	N/A
CX210	N/A	N/A	N/A	250W RMS	CX1060C-16	COAX	4KHz @18dB	38Hz-20KHz	102dB SPL@1W1M	8Ω	20.375"W X 20"H X 16"D	48 LBS	100°	N/A
CX1015	N/A	N/A	N/A	250W RMS	CX1060C8	COAX	4KHz @18dB	30Hz-20KHz	100dB SPL@1W1M	8Ω	20.375"W X 34"H X 16"D	55 LBS	100°	N/A
CXC110	200/330/420W RMS 8/4/2Ω	660W	N/A	200W RMS	CX1060C8	COAX	4KHz @18dB	36Hz-20KHz	98dB SPL@1W1M	8Ω	15.25"W X 20.5"H X 14.5"D	39 LBS	100°	N/A
CXC210	200/330/420W RMS 8/4/2Ω	660W	N/A	300W RMS	CX1060C-16	COAX	4KHz @18dB	38Hz-20KHz	102dB SPL@1W1M	8Ω	20.375"W X 24"H X 16"D	68 LBS	100°	N/A
CXC1015	200/330/420W RMS 8/4/2Ω	660W	N/A	250W RMS	CX1060C8 & 1560F	COAX	4KHz @18dB	30Hz-20KHz	100dB SPL@1W1M	8Ω	20.375"W X 32"H X 16"D	80 LBS	100°	N/A
D112XLT	N/A	N/A	N/A	250W RMS	EC-1260M CAST FRAME	E-2700	2.5KHz @18dB	32Hz-14KHz	103dB SPL@1W1M	8Ω	21"W X 15.25"H X 14.5"D	38 LBS	60°	N/A
D115XL	N/A	N/A	N/A	400W RMS	EC-1500XL CAST FRAME	N/A	N/A	46Hz-3KHz	103dB SPL@1W1M	4/8Ω	23"W X 25.5"H X 18.5"D	57 LBS	60°	N/A
D115XLT	N/A	N/A	N/A	400W RMS	EC-1500XL CAST FRAME	E-2700	3.5KHz @18dB	46Hz-14KHz	103dB SPL@1W1M	4/8Ω	23"W X 25.5"H X 18.5"D	59 LBS	60°	N/A
D118XL	N/A	N/A	N/A	500W RMS	EC-1800 CAST FRAME	N/A	N/A	42Hz-2.5KHz	100dB SPL@1W1M	8Ω	23"W X 27.5"H X 18.5"D	74 LBS	60°	N/A
D210MBX	N/A	N/A	N/A	350W RMS	EC-1060XL CAST FRAME	E-2700	3.5KHz @18dB	62Hz-14KHz	103dB SPL@1W1M	4/8Ω	23"W X 17"H X 15"D	50 LBS	60°	N/A
D210XLT	N/A	N/A	N/A	350W RMS	EC-1060XL CAST FRAME	E-2700	3.5KHz @18dB	48Hz-14KHz	103dB SPL@1W1M	4/8Ω	23"W X 19.5"H X 18.5"D	68 LBS	60°	N/A
D210XST	N/A	N/A	N/A	500W RMS	EC-1060XS CAST FRAME	E-2700	3.5KHz @18dB	30Hz-14KHz	103dB SPL@1W1M	4/8Ω	23"W X 18"H X 18.5"D	59 LBS	60°	N/A
D212XLT	N/A	N/A	N/A	400W RMS	EC-1260F CAST FRAME	E-2700	3.5KHz @18dB	44Hz-14KHz	103dB SPL@1W1M	4/8Ω	23"W X 27.5"H X 18.5"D	74 LBS	60°	N/A
D215XL	N/A	N/A	N/A	400W RMS	EC-1560ES	N/A	N/A	40Hz-3KHz	103dB SPL@1W1M	4/8Ω	23"W X 38.5"H X 18.5"D	106 LBS	60°	N/A
D215XLT	N/A	N/A	N/A	400W RMS	EC-1560ES	E-2700	3.5KHz @18dB	40Hz-14KHz	103dB SPL@1W1M	4/8Ω	23"W X 38.5"H X 18.5"D	108 LBS	60°	N/A
D410XLT	N/A	N/A	N/A	700W RMS	EC-1060XL CAST FRAME	E-2700	3.5KHz @18dB	50Hz-14KHz	106dB SPL@1W1M	4/8Ω	23"W X 27.5"H X 18.5"D	98 LBS	60°	N/A
D410XST	N/A	N/A	N/A	1000W RMS	EC-1060XS CAST FRAME	E-2700	3.5KHz @18dB	36Hz-14KHz	104dB SPL@1W1M	8Ω	23"W X 25"H X 18.5"D	95 LBS	60°	N/A
D610XLT	N/A	N/A	N/A	1050W RMS	EC-1060XL CAST FRAME	E-2700	3.5KHz @18dB	50Hz-14KHz	107dB SPL@1W1M	6Ω	23"W X 38.5"H X 18.5"D	130 LBS	60°	N/A
D810XLT	N/A	N/A	N/A	1400W RMS	EC-1060XL CAST FRAME	E-2700	3.5KHz @18dB	52Hz-14KHz	108dB SPL@1W1M	4/8Ω	23"W X 52.5"H X 18.5"D	225 LBS	60°	N/A
DC112XLT	230/330/420W RMS 8/4/2Ω	660W	N/A	250W RMS	EC-1260ME CAST FRAME	E-2700	2.5KHz @18dB	32Hz-14KHz	103dB SPL@1W1M	8Ω	21.75"W X 19.25"H X 14.5"D	49 LBS	60°	<.05%
DC210XLT	300/500/750W RMS 8/4/2Ω	1000W	N/A	350W RMS	EC-1060XL CAST FRAME	E-2700	3.5KHz @18dB	48Hz-14KHz ±2dB	N/A	8Ω	23"W X 24"H X 18.5"D	78 LBS	60°	<.05%
VT300B	300W RMS	N/A	N/A	N/A	N/A	N/A	N/A	20Hz-15KHz ±2dB	N/A	N/A	19"W X 7"H X 11.5"D	40 LBS	N/A	<.2%
WP100	N/A	N/A	N/A	N/A	N/A	N/A	N/A	10Hz-20KHz ±2dB	N/A	N/A	17"W X 3.5"H X 12"D	8.6 LBS	N/A	<.01%
WT1205	2x500/600 RMS 4/2Ω	2400W	1200/1000W RMS 4/8Ω	N/A	N/A	N/A	N/A	10Hz-20KHz ±2dB	N/A	N/A	17"W X 3.5"H X 13"D	26 LBS	N/A	<.05%
WT1250	2x430/625W RMS 4/2Ω	2500W	1250W RMS @ 4Ω	N/A	N/A	N/A	N/A	10Hz-20KHz ±2dB	N/A	N/A	17"W X 3.5"H X 14.5"D	28 LBS	N/A	<.05%
WT1550	2x600/750W RMS 4/2Ω	3000W	1550W RMS @ 4Ω	N/A	N/A	N/A	N/A	10Hz-20KHz ±2dB	N/A	N/A	17"W X 3.5"H X 14.5"D	32 LBS	N/A	<.05%
WT330	230/330/420W RMS 8/4/2Ω	840W	N/A	N/A	N/A	N/A	N/A	10Hz-15KHz ±2dB	N/A	N/A	13"W X 3.5"H X 12.5"D	13 LBS	N/A	<.05%
WT405	250/405/620W RMS 8/4/2Ω	1300W	N/A	N/A	N/A	N/A	N/A	10Hz-15KHz ±2dB	N/A	N/A	13"W X 3.5"H X 12.5"D	15 LBS	N/A	<.05%
WT550	300/500/620W RMS 8/4/2Ω	1500W	N/A	N/A	N/A	N/A	N/A	10Hz-15KHz ±2dB	N/A	N/A	12"W X 3.5"H X 12"D	20 LBS	N/A	<.05%
WT800B	2 X 440W RMS @ 4Ω	2200W	800W RMS @ 8Ω 1100W RMS @ 4Ω	N/A	N/A	N/A	N/A	10Hz-15KHz ±2dB	N/A	N/A	17"W X 3.5"H X 12"D	26 LBS	N/A	<.05%

Nemesis

Model	Power	Power Handling	Speakers	Tweeter	Crossover	Frequency Response	Sensitivity	Impedance	Dimensions	Weight	Coverage	Distortion
NA320	320W @ 4Ω	N/A	N/A	N/A	N/A	10Hz - 18KHz	N/A	N/A	16"W x 3.5"H x 10"D	15 LBS.	N/A	<.1%
NA650	650W @ 2Ω	N/A	N/A	N/A	N/A	10Hz - 18KHz	N/A	N/A	17"W x 3.5"H x 11"D	18 LBS	N/A	<.1%
NC115	250W @ 4Ω	250W RMS	ES1560-8	T2004	3KHz @ 12dB	38Hz - 18kHz	100dB SPL@1W1M	4Ω	24.75"W x 17.25"H x 16.25"D	42 LBS.	90°	<.1%
NC210	250W @ 4Ω	300W RMS	2 x ES1040XL8	T2004	3KHz @ 12dB	35Hz - 18kHz	102dB SPL@1W1M	4Ω	24.75"W x 16.25"H x 16.25"D	47 LBS.	90°	<.1%
NC212	320W @ 4Ω	350W RMS	2 x ES1260-8	T2004	3KHz @ 12dB	48Hz - 18kHz	102dB SPL@1W1M	4Ω	24.75"W x 24.75"H x 16.25"D	58 LBS.	90°	<.1%
NC410	320W @ 4Ω	500W RMS	4 x ES1040XL16	T2004	3KHz @ 12dB	48Hz - 18KHz	104dB SPL@1W1M	4Ω	24.75"W x 24.75"H x 16.25"D	62 LBS.	90°	<.1%
NC810	400W @ 4Ω	800W RMS	8 x ES1040XL8	T2004	3KHz @ 12dB	42Hz - 18KHz	107dB SPL@1W1M	4Ω	24.75"W x 48.75"H x 16.25"D	120 LBS.	90°	<.1%
NSP115	N/A	250W RMS	ES15608	T2004	3KHz @ 12dB	38Hz - 18KHz	100dB SPL@1W1M	8Ω	24.75"W x 17.25"H x 16.25"D	32 LBS.	90°	N/A
NSP210	N/A	300W RMS	2 x ES1040XL8	T2004	3KHz @ 12dB	35Hz - 18KHz	102dB SPL@1W1M	4/8Ω	24.75"W x 16.25"H x 16.25"D	35 LBS.	90°	N/A
NSP212	N/A	350W RMS	2 x ES12608	T2004	3KHz @ 12dB	48Hz - 18KHz	102dB SPL@1W1M	4Ω	24.75"W x 24.75"H x 16.25"D	48 LBS.	90°	N/A
NSP410	N/A	500W RMS	4 x ES1040XL16	T2004	3KHz @ 12dB	48Hz - 18KHz	104dB SPL@1W1M	4/8Ω	24.75"W x 24.75"H x 16.25"D	50 LBS.	90°	N/A
NSP810	N/A	800W RMS	8 x ES1040XL8	T2004	3KHz @ 12dB	42Hz - 18KHz	107dB SPL@1W1M	4Ω	24.75"W x 48.75"H x 16.25"D	105 LBS.	90°	N/A

Silver Series

Model	Power	Power Handling	Speakers	Tweeters	Crossover	Frequency Response	Sensitivity	Impedance	Dimensions	Weight	Coverage	Distortion
N10S	80/100W RMS 8/4Ω	150W RMS	ES1040	T1004	4KHz @ 12dB	42Hz - 18KHz	97dB SPL@1W1M	8Ω	20.5"W x 16.5"H x 13.25"D	45 LBS.	90°	<.1%
N12S	120/170W RMS 8/4Ω	150W RMS	ES1240	T1004	4KHz @ 12dB	42Hz - 18KHz	98dB SPL@1W1M	8Ω	20.5"W x 21.5"H x 13.25"D	47 LBS.	90°	<.1%
N15S	120/170W RMS 8/4Ω	200W RMS	ES1560	T1004	4KHz @ 12dB	38Hz - 18KHz	99dB SPL@1W1M	8Ω	20.5"W x 25.5"H x 15.5"D	50 LBS.	90°	<.1%
N28S	120/170W RMS 8/4Ω	160W RMS	ES832	T1004	4KHz @ 12dB	40Hz - 18KHz	100dB SPL@1W1M	8Ω	20.5"W x 16.5"H x 13.25"D	47 LBS.	90°	<.1%